

Emitter composition using diamond, method of manufacturing the same and field emission cell using the same

Patent number: CN1581400
Publication date: 2005-02-16
Inventor: YANG WOON NA (KR), GWANG-BAI KIM (KR)
Applicant: ILJIN DIAMOND CO. LTD (KR)
Classification:
 - international: H01J1/304, H01J9/02
 - european: H01J1/304, H01J9/02B2
Application number: CN200410043459 20040429
Priority number(s): KR20030053785 20030804


Also published as:

EP1505621 (A1)
 JP2005056822 (A)

[Report a data error here](#)

Abstract not available for CN1581400
 Abstract of correspondent: **EP1505621**

An emitter composition of a field emission cell that is printed on a cathode substrate of a display to be applied to an electron emission source, including a carbon nanotube, a binder, glass frit, a dispersing agent and an organic solvent, characterized by further having 0.1-20 w% of diamond. A manufacturing method for the emitter composition and a field emission cell using the emitter composition are also provided. Since the field emission cell has the carbon nanotube and the diamond distributed simultaneously therein, it has a relatively high current density even at the same driving voltage, thereby improving emitting properties. In addition, the field emission cell is advantageous in terms of superior printability and stable field emission, while reducing various expenses.



BEST AVAILABLE COPY

required to operate and repair
constitutive parts thereof.

Data supplied from the *esp@cenet* database - Worldwide